




BIO OIL REMOVER INDUSTRIAL CLEANING POWDER



- **BIO OIL REMOVER** does not affect oil separators, which is a great advantage when using the product in garages.
- Special product for cleaning diesel aprons at filling stations. Diesel oil and petrol stains are removed completely.
- **Biodegradable.**
- **Phosphate-free.**

Where to use

Yellow-white, highly active, moderate foaming, "Heavy-Duty" powder, alkaline cleaning compound with a pleasant, fresh pine odour for universal application, bathsystems and steam cleaning apparatus or sprinkling systems.

Safe for steel, stainless steel, copper, brass, magnesium, porcelain, glass, ceramic tiles, plastics, concrete.

Packing

10 kg bucket

How to use

General:

1 - 4 g/l water. Temperature: 20 - 60° C.

Steam cleaning:

8 g/l water at steampressure of 18 kilos or more.

Floor/apron cleaning:

2 - 30 g/l water. Temperature: 20 - 60° C. or apply on wet soiled areas, sprinkle on **BIO OIL REMOVER**, brush it in before rinsing.

Radiator cleaning:

10 - 40 g/l. Circulate.

Immersion tank:

30 - 75 g/l. Temperature: 70 - 80° C.

Filth cleaning:

5 - 10 g/l. Temperature: 49 - 60° C.

Note: In all cases: rinse thoroughly with clear water afterwards!

Eigenschappen

Physical aspect	:	yellow-white powder
pH 5% solution	:	13,0 ± 0,5
Odor	:	pine
Solubility in water	:	limited

Safety

The safety information of this product is mentioned in our Safety Data Sheet (MSDS).
If using cleaning- and/or disinfectant products use always personal protective equipment.

* Only to be used by professional users.